

MODEL DHH4-20SDRX

EXPLOSION PROOF REFRIGERATOR 1°C TO 10°C

Capacity [Cu. Ft.]	20 Cu. Ft.
Capacity [Liters]	566 Liters
Temperature Range [°C]	1°C to 10°C
Temperature Range [°F]	33°F to 50°F

Dimensions	Width x Depth x Height
Exterior [Inches]	34.75" x 29" x 74.5"
Interior [Inches]	24.75" x 20.75" x 65.25"
Exterior [Centimeters]	88 x 74 x 189
Interior [Centimeters]	63 x 53 x 166

Compressor	Hermetic Compressor
Air Circulation	Forced Air
Defrost Method	Cycle
Refrigerant	R600a
Exterior	Painted Steel
Interior	Painted Steel
Insulation	High Density Urethane
Lockable Door	1 Door, Keyed Lock
Door Material	Insulated Steel
Leveling Legs	4
Storage	5 Adjustable Shelves
Shipping Weight	260 lbs.

Electrical

Voltage:	115 Volts 60 Hertz 1 Phase
Amperage Line Running	15 Amp Dedicated 3A
Electrical Plug	Not Supplied (Hardwired)
Certification(s)	ETL Listed

Controller

Display Type	Microprocessor, Digital
Alarms	High/Low Temp
Min / Max Temperature	Display and Reset
Alarm Relay	Dry Contacts

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



» **Meets NFPA / OSHA Guidelines for Hazardous Locations Class 1, Division II, Group C & D**

Warranty 2 Years Parts & Labor.