

MODEL NU40-18

UPRIGHT ULTRA LOW FREEZER 0°C TO -40°C

Capacity [Cu. Ft.]	18 Cu. Ft.
Capacity [Liters]	505 Liters
Temperature Range [°C]	0°C to -40°C
Temperature Range [°F]	32°F to -40°F
Dimensions	Width x Depth x Height
Exterior [Inches]	36" x 36" x 79.5"
Interior [Inches]	23" x 26" x 51.25"
Exterior [Centimeters]	101 x 91 x 201
Interior [Centimeters]	58 x 66 x 130
Refrigeration System	Single Stage System
Compressors	1, Hermetic Compressor
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Inner Doors	5, Stainless Steel
Lockable Door	Lockable with Padlock
Porthole	Optional 1/2"
Casters	4, Swivel with Locks
Storage Shelves	4 Adjustable, 1 Base Shelf
Shipping Weight	900 Lbs.

Electrical

Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug (Optional Voltages)	20A 7.3A NEMA 5-20 208 Volts, 230 Volts
Certification(s)	ETL Listed

Controller

Display Type	Microprocessor, Digital
Touchscreen	Yes, 4.3" Color Display
Alarms	High/Low Temp, Power Failure, Low Battery
Alarm Notification	Yes, Audible, Email, Text
Data Logging	Yes, Adjustable Intervals
Data Download	Yes, via USB, CSV Format
LAN Remote Access	Yes, via VNC
Min / Max Temperature	Yes, Display and Reset
Alarm Relay	Yes, Dry Contacts
Automatic Restart	Yes, After Power Failure
Backup Battery	Yes, Only Powers Alarm

Warranty 1 Year Parts & Labor

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES

