

ENGINEERS AND MANUFACTURERS OF ULTRA-LOW FREEZERS

Sheldon Refrigerated Incubator Model SRI3

**2.4 Cu. Ft. Upright
Temperature Range: 0°C to 45°C**

Specifications:

* Capacity	2.4 Cubic Ft.
* Temperature Range	0°C to 45°C
* Dimensions	
* Exterior w x d x h	24 x 21 x 33.8" 61 x 53.4 x 85.8 (cm)
* Interior w x d x h	16 x 14 x 22.5" 40.7 x 35.6 x 57.2 (cm)

Design Information:

The SRI3 space-saving low temperature incubator is ideal for small volume workloads and meets APHA specifications for Biochemical Oxygen Demand (B.O.D.) analysis.



Units are equipped with a hermetically-sealed compressor, a circuit breaker to protect from electrical overload, and an easy-to-clean fully insulated chamber that is corrosion-resistant. Gentle, continuous forced-air circulation ensures temperature uniformity and reproducible test conditions. Each unit also includes an independent over temperature safety controller, two shelves (adjustable in two inch increments), and a one amp interior outlet to allow the use of shakers, stirrers, roller bottles or other apparatus. This unit has a steel exterior with welded Seams and corners and a double-coated, baked enamel finish. It is supplied with Adjustable leveling feet and a condensation drip tray. Low Temperature Incubators are ideal for testing B.O.D. of sewage and waste water, as well as other low and room temperature applications.

Features:

- Microprocessor Control**
- P.I.D. Temperature Control**
- LED Display of Setpoint and Chamber Temperature**
- High Limit Thermostat**
- Interior Electrical Outlet**
- Fan Assisted/Forced-Air Circulation**
- Hermetically Sealed Compressor**
- 24 Month Limited Warranty**

Specifications subject to change without notice